


SIDE VIEW






SIDE VIEW

GENERAL NOTE






- CONTACT SOM PROJECT MGR. FOR ELEVATOR NUMBER.
- SWING RETURN DUST COVER & HINGES SUPPLIED & INSTALLED BY CAB MANUFACTURER.
- ALL PUSHBUTTONS AND INDICATORS TO BE S-BUTTON STYLE.
- ▲ KEYSWITCHED TO BE SCHLAGE TYPE LOCKS W/ REMOVABLE CONSTRUCTION CORES KEYED 1246 TO MATCH EXISTING STANFORD STANDARDS.
- BRAILLE TO HAVE WHITE CHARACTERS ON A BLACK BACKGROUND.
- BUTTONS ARE 0.125 PROJECTING FLAT SURFACE WITH SQUARE SHOULDERS.

GENERAL LEGEND		VOLTAGE		PUSHBUTTON CONTACTS		NO. INC.	
A	SIGNATIC DIGITAL P.L.	ILLUM. PUSHBUTTONS	24 VDC	FLOOR PUSHBUTTON GHD0			
B	EMERGENCY LIGHT BATTERY	ALL OTHER DEVICES	24 VDC	DOOR OPEN GHD0			
C	EMERGENCY LIGHT	ALARM BUTTON ILLUMINATES 12 VOLTS VIA EMERGENCY LIGHT BATTERY		DOOR CLOSE GHD0			
D	FIRE SERVICE INDICATOR	ALL FIRE SERVICE OPERATIONS HALOS ARE RED		CALL CANCEL (VER)			
E	2004 PHASE II CABINET SIZE: 7.0 (177.80 mm) W x 10.0 (254.00 mm) H	ALL MEDICAL EMERGENCY OPERATIONS HALOS ARE BLUE		ALARM GHD0			
F	SETSMIC INDICATOR	ALL HALOS ARE BLACK					
G	ACU SPEECH UNIT	BRAILLE ADA COMPLIANT		PREVIRE TO SPEC	YES	NO	
H	6X6 BRONZE ACRYLIC LENS FOR CUST. SUPPLIED & INSTALLED CARD READER	1.250 (31.75 mm) SQ.					
I	PUSH TO CALL PUSHBUTTON W/ PHONE & HELP BRAILLE COMBO	INCLUDES					
J	VAUTEC 911-900 10W HANDSFREE PHONE MOUNTED BEHIND PANEL	K	T	SWITCH IDENTIFICATION	OPERATING POSITIONS	KEY POSITION	PREVIOUS POSITION
K	PROVISIONS FOR CUSTOMER SUPPLIED & INSTALLED INTERCOM	F	G	FIREMAN	OFF - HOLD-ON	ALL	ALL
L	80V X 4.25H CERTIFICATE WINDOW			STOP	STOP - RUN	ALL	ALL
M	110V X 12.0H SERVICE CABINET			LIGHT	OFF - ON	ALL	ALL
				FAN	OFF - ON	ALL	ALL
				END SVC	OFF - ON	ALL	ALL
				ACCESS ENABLE	OFF - ON	ALL	ALL
				CHAMBER INVERSE	OFF - ON	ALL	ALL
				VOICE - TONE	ALL	ALL	▲ VER
				ON - OFF		ALL	VER
				ON - OFF		ALL	VER
				EMERGENCY LIGHT TEST PUSHBUTTON			
				GFI OUTLET			
				NOTE: KEY SWITCH FINISH TO MATCH COVERPLATE MATERIAL.			







WD #496875
SERVICE CABINET SUBPLATE LAYOUT
 MOUNTED BEHIND LOCKED DOOR
 DEVICE STYLE: UNIVERSAL, ROUND, PROJECTING
 MATERIAL: 11 GA. #4 STAINLESS STEEL
 SCALE: 2.000 (50.80 mm) = 1.000 (25.40 mm)



2004 ANSI FIRE CABINET SUBPLATE LAYOUT
 MOUNTED BEHIND LOCKED DOOR
 DEVICE STYLE: UNIVERSAL, ROUND, PROJECTING
 MATERIAL: 18 GA. BLACK VINYL
 SCALE: 2.000 (50.80 mm) = 1.000 (25.40 mm)



GENERAL NOTE
 1. ALL PUSHBUTTONS TO BE S-BUTTON STYLE

KEY	IDENT	SWITCH IDENTIFICATION	OPERATING POSITIONS	KEY REMOVE POSITION	INDICATED POSITION	INDIC. PNL.	KEY CODE	REMARK
FREE SERVICE CABINET DEVICE LEGEND								
•	•	FIRE OPERATION	OFF - HOLD - ON	OFF-HOLD	ALL		SIS	
•	•	STOP	RUN - STOP		ALL			
•	•	DOOR OPEN PUSHBUTTON						
•	•	DOOR CLOSE PUSHBUTTON						
•	•	CALL CANCEL PUSHBUTTON						
•	•	FIREMAN'S PHONE JACK						
INCLUDED IN SERVICE CABINET								
•	•	STOP	STOP - RUN	ALL	ALL		▲	VER
•	•	LIGHT	OFF - ON	ALL	ALL		▲	VER
•	•	FAN	OFF - ON	ALL	ALL		▲	VER
A	0.125 (3.18 mm)	DIB SVC	OFF - ON	ALL	ALL		▲	VER
B	0.126 (3.17 mm)	ACCESS ENABLE	OFF - ON	ALL	ALL		▲	VER
C	0.188 (4.76 mm)	CARDREADER OVERRIDE	OFF - ON	ALL	ALL		▲	VER
D	0.250 (6.35 mm)		VOICE - TONE	ALL	ALL		▲	VER
E	0.375 (9.53 mm)		ON - OFF		ALL			VER
F	0.500 (12.70 mm)		ON - OFF		ALL			VER
G	0.750 (19.05 mm)	EMERGENCY LIGHT TEST PUSHBUTTON						
H	1.000 (25.40 mm)	GFI OUTLET						
I	FILL BLACK							
Z	FILL RED							

NOTE: KEY SWITCH FINISH TO MATCH COVERPLATE MATERIAL.



STANFORD UNIVERSITY
 Facilities, Information & Technology

FLOOR:


By: Tim Lee

Rev: 12/07/2010


CAR OPERATING PANEL

TERMINAL HALL STATION
QTY: 2 REQ'D TOTAL



WD #496895 / H1 / QTY: 1 REQ'D UP @ FLOOR G
WD #496897 / H4 / QTY: 1 REQ'D DOWN @ FLOOR 3




WD #496899
H2
TERMINAL HALL STATION
QTY: 1 REQ'D L
REQ'D @ FLOOR 1



WD #496901
H3
TERMINAL HALL STATION
QTY: 1 REQ'D L
REQ'D @ FLOOR 2




- GENERAL NOTE**
- FOR CABLE INFO. SEE WORK INSTRUCTION # W11141 CABLE MATRIX.
 - FOR WARNING INFO. SEE WORK INSTRUCTION # W11153.
 - ALL PUSHBUTTONS TO BE S-BUTTON STYLE.
 - BUTTONS ARE 0.125 PROJECTING FLAT SURFACE WITH SQUARE SHOULDERS.



VOLTAGE		FASTENERS		ENGRAVING FONT			
BLINK PB 24 VDC		CONCEALED		HELVETICA LIGHT QUAD.			
ALL OTHER 24 VDC		BUTTONHEAD		A	0.125 (3.18 mm)	F	0.500 (12.70 mm)
BEVELED EDGES		YES	NO	B	0.156 (3.97 mm)	G	0.750 (19.05 mm)
DEVICE STYLE				C	0.188 (4.76 mm)	H	1.000 (25.40 mm)
PUSHBUTTON	PB-27	KEYSWITCH	PS-1	D	0.250 (6.35 mm)	I	FILL BLACK
INDICATOR	PS-1	TOGGLE		E	0.375 (9.53 mm)	J	FILL RED
LAMPS	RED LED	HALD		PB CONTACTS		NO/UNC	
ALL FIRE SERVICE & EMERGENCY OPERATED HALD ARE RED.				CALL PB'S			
ALL BLUE HALD, NORMAL, EMERGENCY, HOSPITAL, EMERGENCY AND EMERGENCY SERVICE OPERATED HALD ARE BLUE.				DOOR OPEN			
LANTERN COLOR				DOOR CLOSE			
AUXILIARY SIGNAL				DOOR STOP			
EMERG TEST				EMERG TEST			
BRAILLE ADA COMPLIANT							
1.250 (31.75 mm) S3				1.375 (34.93 mm) DIA CCS-SH-3			
KEYSWITCH AND TOGGLE LEGEND							
KEY	SWITCH IDENTIFICATION	OPERATING POSITIONS	KEY SERVICE POSITION	OPERATING POSITION	INITIAL POS.	KEY CODE	KEY MARK
B	C	FIRE RECALL	RESET-OFF-ON	OFF-ON	ALL		SUS HIR
NOTE: KEY SWITCH FINISH TO MATCH COVERPLATE MATERIAL.							
GENERAL LEGEND							
A: KNOCKOUT FOR 0.500 (12.70 mm) DIA							


WD #3496903
L1

TERMINAL HALL DIRECTIONAL LANTERN
QTY: 2 REQ'D
REQ'D @ FLOOR B




WD #496905
L2

TERMINAL HALL DIRECTIONAL LANTERN
QTY: 2 REQ'D
REQ'D @ FLOOR 3




WD #496907
L3

TERMINAL HALL DIRECTIONAL LANTERN
QTY: 2 REQ'D
REQ'D @ FLOOR 2




WD #496907
L3

TERMINAL HALL DIRECTIONAL LANTERN
QTY: 2 REQ'D
REQ'D @ FLOOR 2



DIGITAL P.J. CUTOUT & STUDDING DETAIL




GENERAL NOTE

- FOR CABLE INFO. SEE WORK INSTRUCTION # W11141 CABLE MATRIX.
- FOR WARNING INFO. SEE WORK INSTRUCTION # W11153.

VOLTAGE		FASTENERS		ENGRAVING FONT			
ILLUM. PS		CONCEALED		HELVETICA LIGHT COND.			
ALL OTHERS VDC		SECURITY		A	0.125 (3.18 mm)	F	0.500 (12.70 mm)
BEVELED EDGES		YES	NO	B	0.156 (3.97 mm)	G	0.750 (19.05 mm)
DEVICE STYLE				C	0.180 (4.76 mm)	H	1.000 (25.40 mm)
PUSHBUTTON		KEYSWITCH		D	0.250 (6.35 mm)	I	FILL BLACK
INDICATOR		TOGGLE		E	0.375 (9.53 mm)	J	FILL RED
LAMPS		HALO		PB CONTACTS		NO/NC	
ALL PBE SERVICE & EMERGENCY OPERATED HALO ARE RED.				CALL PS'S			
ALL CONC. BLK, NORMAL EMERGENCY, HOSPITAL EMERGENCY AND EMERGENCY SERVICE OPERATED HALO ARE BLUE.				DOOR OPEN			
LANTERN COLOR				AUXILIARY SIGNAL		DOOR STOP	
UNPUSHED LED	EMERGENCY LED	NO GEM		EMERG. TEST			
BRAILLE ADA COMPLIANT							
1.250 (31.75 mm) SQ.		1.375 (34.93 mm) DIA. CCS-SH-B					
KEYSWITCH AND TOGGLE LEGEND							
KEY	SWITCH IDENTIFICATION	OPERATING POSITIONS	KEY NUMBER	OPERATED POSITION	UNOPERATED POSITION	KEY CODE	KEY TYPE
NOTE: KEY SWITCH FINISH TO MATCH COVERPLATE MATERIAL							
GENERAL LEGEND							
A KNEECUT FOR 0.500 CONDUIT							
B POSITION INDICATOR IS HOME SIGNALIC DOT MATRIX 60007							



WD #496914
A2
FIRE KEY CABINET
QTY: 1 REQ'D





GENERAL NOTE

1. FOR CABLE INFO, SEE WORK INSTRUCTION # W11141 CABLE MATRIX.
2. FOR WARNING INFO, SEE WORK INSTRUCTION # W11153.
3. ● KEYSWITCHES TO BE SCHLAGE TYPE LOCKS W/ REMOVABLES CONSTRUCTION CORES KEYED 1246 TO MATCH EXISTING STANFORD STANDARDS.

WD #496913
A1
HOISTWAY ACCESS STATION
MOUNTED IN ENTRANCE JAMB AT TERMINAL LANDING
QTY: 4 REQ'D.

FIRE KEY CABINET SUBPLATE
MOUNTED BEHIND LOCKED DOOR
MATERIAL: 18 GA. COLD ROLL
FINISH: PAINT FLAT BLACK
SCALE: 1.000 (25.40 mm) = 1.000 (25.40 mm)



VOLTAGE	FASTENERS	ENGRAVING FONT						
ILLUM. PB	SECURITY	HELVETICA LIGHT OUNED.						
ALL OTHER	BUTTONHEAD	A 0.125 (3.18 mm)	F 0.500 (12.70 mm)					
BEVELED EDGES	YES	NO B 0.156 (3.97 mm)	G 0.750 (19.05 mm)					
DEVICE STYLE		C 0.188 (4.76 mm)	H 1.000 (25.40 mm)					
PUSHBUTTON	KEYSWITCH	D 0.250 (6.35 mm)	I 1.000 (25.40 mm)					
INDICATOR	TOGGLE	E 0.375 (9.53 mm)	J 2.000 (50.80 mm)					
LAMPS	HALO	BLACK	PB CONTACTS		NO/NC			
ALL FIRE SERVICE & EMERGENCY OPERATION HALOS ARE RED.		CALL PB'S						
ALL CODE BLUE, MEDICAL EMERGENCY, HOSPITAL EMERGENCY AND EMERGENCY SERVICE OPERATION HALOS ARE BLUE.		DOOR OPEN						
LANTERN COLOR		ALUDDLE SIGNAL	DOOR CLOSE					
UP	DOWN	EMERG TEST						
BRILLE ADA COMPLINT								
1.250 (31.75 mm) SQ.		1.375 (34.93 mm) DIA. CCS-SH-B						
KEYSWITCH AND TOGGLE LEGEND								
KEY	IND	SWITCH IDENTIFICATION	OPERATING POSITIONS	KEY REMOVE POSITION	UNREMOVED POSITION	HEMEL. PNL.	KEY CODE	HEMEL.
B		ACCESS	UP - OFF -DN	OFF	OFF	UP-DN	●	VER
NOTE: KEY SWITCH FINISH TO MATCH COVERPLATE MATERIAL.								
GENERAL LEGEND								
A		KNOCKOUT FOR 0.500 CONDUIT						
C		KNOCKOUT FOR 1.250 CONDUIT						
D		2.000 DIA. ESCUTION PLATE						

